

PRODUCT DATA SHEET

Picto 100 Halo Horizontal Ceiling - FL - Black



DESIGN BY:

Artemide

MATERIALS:

Aluminium and polyamide

DESCRIPTION:

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: #70mm, #100mm and #125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°, Precise inclination by means of a graduation specially designed, with a locking mechanism.

Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear, Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards. standards

Optic FL (2x15° < angle < 2x20°)

Light emission



Accent Lighting



-0-

TECHNICAL DATA SHEET

Features

Product name: Picto 100 Halo Horizontal Ceiling -FL - Black

M224941FL Black

Material: Aluminium and polyamide

Series: Architectural **Environment:** Indoor

Area contract: Retail, Museum & Exihibitions,

Private Residence

OPTICS

Article Code:

Colour:

Emission: Accent Lighting

DIMENSIONS

Length: (cm) 13.2 Height: (cm) 11.1 (cm) 4.4 Depth: (cm) 10 Cutout width: Inclination: -90+90 355 Rotation:


Cutout shape:

1.6 Weight: Glow Wire Test:

LAMPS NOT INCLUDED

Category: HALO Number: Qt12-lp Lbs: Watt: 60 Gy6.35 Socket: Type: N/s Colour Rendering: 1a Colour temperature (K): 3000 Duration (h):

Dimensions



LAMP





ELECTRICAL

Trasformer availability: Transformer voltage:

Emergency availability: Dimmable by trailing or leading edge external dimmers

220V-240V

Integrated

20-60W

Voltage:



ACCESSORIES



PICTO 100 - Accessoryholder + Louvre (black). White M081717



PICTO 100 - Accessoryholder + wall washer screen (black). white M082717



PICTO 100 - Accessoryholder + Adjustable dowser (black). white M082617



PICTO 100 HIT - UV-Filter. M080545