

PRODUCT DATA SHEET

Picto 100 Vertical Ceiling - HIT 35W SP - White/Anthracite grey

**DESIGN BY :**

Artemide

MATERIALS :

Aluminium and polyamide

DESCRIPTION :

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: $\varnothing 70\text{mm}$, $\varnothing 100\text{mm}$ and $\varnothing 125\text{mm}$. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90° , rotation of up to 355° . Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic SP ($2 \times 5^\circ$ < angle < $2 \times 10^\circ$)Optic MFL ($2 \times 10^\circ$ < angle < $2 \times 15^\circ$)Optic FL ($2 \times 15^\circ$ < angle < $2 \times 20^\circ$)Optic WFL ($2 \times 20^\circ$ < Angle < $2 \times 30^\circ$)**Light emission**


Accent Lighting

IP20  

TECHNICAL DATA SHEET

Features

Product name:	Picto 100 Vertical Ceiling - HIT 35W SP - White/Anthracite grey
Article Code:	M224221SP
Colour:	White/Anthracite grey
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

Dimensions**OPTICS**

Emission: Accent Lighting

DIMENSIONS

Length:	(cm) 9.2
Height:	(cm) 16.5
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	$-90+90$
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-TC-CE
Watt:	35
Socket:	G8.5
Type:	MT/UB-35
Luminous Flux (lm):	3000
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	9000

LAMPIP20  **ELECTRICAL**

Starter:	Electronics integrated
Voltage:	220V-240V

ACCESSORIES



PICTO 100 - Accessory-holder + Louvre (black). anthracite-grey M081727



PICTO 100 - Accessory-holder + wall washer screen (black). anthracite-grey M082727



PICTO 100 - Accessory-holder + Adjustable dowser (black). anthracite-grey M082627



PICTO 100 HIT - UV-Filter. M080545