

## PRODUCT DATA SHEET

### Picto 100 Vertical Ceiling - HIT 35W WFL - Silver



#### DESIGN BY :

Artemide

#### MATERIALS :

Aluminium and polyamide

#### DESCRIPTION :

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes:  $\varnothing 70\text{mm}$ ,  $\varnothing 100\text{mm}$  and  $\varnothing 125\text{mm}$ . 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminium optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from  $-90^\circ$  to  $90^\circ$ , rotation of up to  $355^\circ$ . Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic WFL ( $2 \times 20^\circ < \text{Angle} < 2 \times 30^\circ$ )

#### Light emission



Accent Lighting


IP20

### TECHNICAL DATA SHEET

#### Features

Product name:	Picto 100 Vertical Ceiling - HIT 35W WFL - Silver
Article Code:	M224261WFL
Colour:	Silver
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

#### Dimensions



#### OPTICS

Emission:	Accent Lighting
-----------	-----------------

#### DIMENSIONS

Length:	(cm) 9.2
Height:	(cm) 16.5
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	$-90+90$
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

#### LAMP

IP20

#### ELECTRICAL

Starter:	Electronics integrated
Voltage:	220V-240V

#### LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-TC-CE
Watt:	35
Socket:	G8.5
Type:	MT/UB-35
Luminous Flux (lm):	3000
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	9000

## ACCESSORIES

---



PICTO 100 HIT - UV-Filter.  
M080545



PICTO 100 - Accessory-  
holder + Louvre (black).  
Black M081737



PICTO 100 - Accessory-  
holder + wall washer  
screen (black). Black  
M082737



PICTO 100 - Accessory-  
holder + Adjustable  
dowser (black). black  
M082637