

PRODUCT DATA SHEET

Picto 100 Halo Vertical Ceiling - SP - Black



DESIGN BY :

Artemide

MATERIALS :

Aluminium and polyamide

DESCRIPTION :

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: $\varnothing 70\text{mm}$, $\varnothing 100\text{mm}$ and $\varnothing 125\text{mm}$. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminium optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90° , rotation of up to 355° . Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic SP ($2 \times 5^\circ < \text{angle} < 2 \times 10^\circ$)

Light emission



Accent Lighting



TECHNICAL DATA SHEET

Features

Product name:	Picto 100 Halo Vertical Ceiling - SP - Black
Article Code:	M224441SP
Colour:	Black
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

OPTICS

Emission:	Accent Lighting
-----------	-----------------


DIMENSIONS

Length:	(cm) 9.2
Height:	(cm) 16.5
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	$-90+90$
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	Qt12-lp
Watt:	60
Socket:	Gy6.35
Type:	N/s
Colour Rendering:	1a
Colour temperature (K):	3000
Duration (h):	4000

Dimensions



LAMP



ELECTRICAL

Transformer availability:	Integrated
Transformer voltage:	20-60W
Emergency availability:	Dimmable by trailing or leading edge external dimmers.
Voltage:	220V-240V

ACCESSORIES



PICTO 100 - Accessory-
holder + Louvre (black).
White M081717



PICTO 100 - Accessory-
holder + wall washer
screen (black). white
M082717



PICTO 100 - Accessory-
holder + Adjustable
dowser (black). white
M082617