

## PRODUCT DATA SHEET

### Picto 100 LED Horizontal Ceiling - 19W 4000K SP Dimmable - Black/White

**DESIGN BY :**

Artemide

**MATERIALS :**

Aluminium and polyamide

**DESCRIPTION :**

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes:  $\varnothing 70\text{mm}$ ,  $\varnothing 100\text{mm}$  and  $\varnothing 125\text{mm}$ . 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from  $-90^\circ$  to  $90^\circ$ , rotation of up to  $355^\circ$ . Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic SP ( $2 \times 5^\circ < \text{angle} < 2 \times 10^\circ$ )**Light emission**

Accent Lighting



### TECHNICAL DATA SHEET

**Features**

Product name:	Picto 100 LED Horizontal Ceiling - 19W 4000K SP Dimmable - Black/White
Colour:	Black/White
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

**OPTICS**


Emission:	Accent Lighting
-----------	-----------------

**DIMENSIONS**

Length:	(cm) 13.2
Height:	(cm) 12.6
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	$-90+90$
Rotation:	355
Cutout shape:	
Weight:	1.7
Glow Wire Test:	850 °

**LAMPS INCLUDED**

Category:	LED
Watt:	19
Typology:	Led
Color Rendering:	1b
Color temperature (K):	4100

**Dimensions****LAMP****ELECTRICAL**

Trasformer availability:	Dimmable DALI
Voltage:	220V-240V

## ACCESSORIES

---



PICTO 100 - Accessory-holder + Louvre (black). White M081717



PICTO 100 - Accessory-holder + wall washer screen (black). white M082717



PICTO 100 - Accessory-holder + Adjustable dowser (black). white M082617