


PRODUCT DATA SHEET

Nothing86System SA Suspension Led Diff - 30W 3000K dimmable - Direct Emission - Anodized



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (Nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Luminaire comes complete with DALI power supply unit.

Light emission



TECHNICAL DATA SHEET

Features

Product name:	Nothing86System SA Suspension Led Diff - 30W 3000K dimmable - Direct Emission - Anodized
Article Code:	M227360
Colour:	Anodized
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor

DIMENSIONS

Length:	(cm) 118
Width:	(cm) 9.2
Height:	(cm) 12.5
Cutout shape:	
Glow Wire Test:	850 °

LAMPS INCLUDED

Category:	LED
Watt:	30
Typology:	Led Bianco
Color Rendering:	N/s
Color temperature (K):	3000

Dimensions



LAMP



ELECTRICAL

Starter:	Electronic Dimmable Dali Integrated
Voltage:	220V-240V