PRODUCT DATA SHEET

Nothing86System SA Ceiling Fluo Darklight - T16 2x28-54W Dimmable - White



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, LED and metal halide technologies can be freely alternated. Pre-wired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (STAND-ALONE) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Light emission



TECHNICAL DATA SHEET

Features

Product name:	Nothing86System SA Ceiling Fluo Darklight - T16 2x28-54W Dimmable - White
Article Code:	M228721
Colour:	White
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Retail, Office

117 9.2 12.5

DIMENSIONS

Length:	(cm)
Width:	(cm)
Height:	(cm)
Cutout shape:	
Glow Wire Test:	850

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Туре:	FDH-54
Luminous Flux (Im):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

| | 125 1174/2348 LAMP IP20 🛈 +0-ELECTRICAL

Starter: Voltage:

Dimensions

Electronic Dimmable DALI Integrated 220V-240V