PRODUCT DATA SHEET

Nota Bene Suspension 1200 - T16 1x54W - White



DESIGN BY :

Artemide

MATERIALS :

Painted Steel

DESCRIPTION :

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps.Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 2416mm.Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis . Light output ratio: 91% (1xT16) and 87% (2xT16).Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16).Electronic ballast or Dali-Switchdim dimmable electronic ballast. The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors.Electrical connectors via quick connectors. Quick adjustment steel suspension cables . Complies with standard EN60598-1 and other specific standards.

Light emission



IP20 🛈 🌃 🕅



Features

OPTICS Emission:

Length:

Width:

Height:

DIMENSIONS


Cutout shape: Weight:

Glow Wire Test:

Product name:

Article Code: Colour: Material: Series: Environment: Area contract: Nota Bene Suspension 1200 - T16 1x54W - White M107020 White Painted Steel Architectural Indoor

Dimensions



LAMP

IP20 🛈 🌆 🕅

ELECTRICAL

Starter: Voltage: Electronic Integrated 220V-240V

LAMPS NOT INCLUDED Category: FLUO Number: Lbs: T16 54 Watt: G5 Socket: FDH-54 Type: Luminous Flux (Im): 4450 Colour Rendering: 85

Colour temperature (K):

Duration (h):

(cm) 16 (cm) 4.8 4.1 850 °

Indirect/Direct

(cm) 123

3000

20000