

## PRODUCT DATA SHEET

### Nota Bene Suspension 2400 - T16 2x54W - White



#### DESIGN BY :

Artemide

#### MATERIALS :

Painted Steel

#### DESCRIPTION :

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps. Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 2416mm. Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m<sup>2</sup> limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio: 91% (1xT16) and 87% (2xT16). Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16). Electronic ballast or Dali-Switchdim dimmable electronic ballast. The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors. Electrical connection via quick connectors. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

#### Light emission



Indirect/Direct

IP20

### TECHNICAL DATA SHEET

#### Features

Product name:	Nota Bene Suspension 2400 - T16 2x54W - White
Article Code:	M107220
Colour:	White
Material:	Painted Steel
Series:	Architectural
Environment:	Indoor
Area contract:	

#### OPTICS

Emission:	Indirect/Direct
-----------	-----------------


#### DIMENSIONS

Length:	(cm) 241
Width:	(cm) 16
Height:	(cm) 4.8
Cutout shape:	
Weight:	7.9
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

#### Dimensions



#### LAMP

IP20

#### ELECTRICAL

Starter:	Electronic Integrated
Voltage:	220V-240V