

PRODUCT DATA SHEET

Nota Bene Suspension 2400 - T16 4x54W - White



DESIGN BY :

Artemide

MATERIALS :

Painted Steel

DESCRIPTION :

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps. Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 2416mm. Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio: 91% (1xT16) and 87% (2xT16). Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16). Electronic ballast or Dali-Switchdim dimmable electronic ballast. The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors. Electrical connection via quick connectors. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

Light emission



Indirect/Direct

IP20

TECHNICAL DATA SHEET

Features

| | |
|----------------|--|
| Product name: | Nota Bene Suspension 2400 - T16 4x54W - White |
| Article Code: | M107320 |
| Colour: | White |
| Material: | Painted Steel |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

OPTICS

| | |
|-----------|-----------------|
| Emission: | Indirect/Direct |
|-----------|-----------------|


DIMENSIONS

| | |
|-----------------|----------|
| Length: | (cm) 241 |
| Width: | (cm) 16 |
| Height: | (cm) 4.8 |
| Cutout shape: | |
| Weight: | 8.1 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 4 |
| Lbs: | T16 |
| Watt: | 54 |
| Socket: | G5 |
| Type: | FDH-54 |
| Luminous Flux (lm): | 4450 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 20000 |

Dimensions



LAMP

IP20

ELECTRICAL

| | |
|----------|-----------------------|
| Starter: | Electronic Integrated |
| Voltage: | 220V-240V |