# **Artemide**

# PRODUCT DATA SHEET

## Nota Bene Ceiling 1200 Darklight - T16 54W + Emergency - Grey



#### **DESIGN BY :**

Artemide

#### MATERIALS :

#### Painted Steel

#### **DESCRIPTION:**

Single ceiling lights using 1x54W or 2x54W T16 fluorescent light source. Two lighting options : dark light and wall washer. Steel body with a white or grey paint finish. Electronic control gear, with or without dimming (Dali-Switchdim). Lamps can be maintained without removing the luminaire. Complies with standard EN60598-1 and other specific standards.

#### Nota Bene ceiling dark light

Super pure aluminum dark light optics. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m<sup>2</sup> limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio 71%. Emergency lighting as an optional extra.

#### Nota Bene ceiling wall washer

Asymmetric aluminum reflector.

#### Light emission



IP20 🛈 🌃 🕅

#### **TECHNICAL DATA SHEET**

### Features

Product name:

Article Code: Colour: Material: Series: Environment: Area contract: Nota Bene Ceiling 1200 Darklight -T16 54W + Emergency - Grey M109097 Grey Painted Steel Architectural Indoor

#### OPTICS

Emission:

Direct

#### DIMENSIONS

Length:	(cm) 123
Width:	(cm) 16
Height:	(cm) 5.4
Cutout shape:	
Weight:	4.8
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	54
Socket:	G5
Туре:	FDH-54
Luminous Flux (Im):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

# | 86 \_\_\_\_\_ | 54 \_\_\_\_\_\_ | 86 \_\_\_\_\_ | 54

1170

# LAMP

IP20 🛈 🌃 🕅

### ELECTRICAL

Starter: Emergency availability: Emergency duration: Voltage: Electronic Integrated Integrated 1 hours 220V-240V

### Dimensions