

## PRODUCT DATA SHEET

### Nota Bene Ceiling 2400 Darklight - T16 2x28-54W Dimmable - Grey

**DESIGN BY :**

Artemide

**MATERIALS :**

Painted Steel

**DESCRIPTION :**

Single ceiling lights using 1x54W or 2x54W T16 fluorescent light source. Two lighting options : dark light and wall washer. Steel body with a white or grey paint finish. Electronic control gear, with or without dimming (Dali-Switchdim). Lamps can be maintained without removing the luminaire. Complies with standard EN60598-1 and other specific standards.

**Nota Bene ceiling dark light**

Super pure aluminum dark light optics. Dark light emission is in compliance with EN12464-1 standard, with average luminance levels lower than the 1000 cd/m<sup>2</sup> limit for an observation angle of 65° or above with respect to the vertical axis. Light output ratio 71%. Emergency lighting as an optional extra.

**Nota Bene ceiling wall washer**

Asymmetric aluminum reflector.

**Light emission**

Direct



### TECHNICAL DATA SHEET

**Features**

Product name:	Nota Bene Ceiling 2400 Darklight - T16 2x28-54W Dimmable - Grey
Article Code:	M109191
Colour:	Grey
Material:	Painted Steel
Series:	Architectural
Environment:	Indoor
Area contract:	

**OPTICS**





Emission:	Direct
-----------	--------

**DIMENSIONS**

Length:	(cm) 248
Width:	(cm) 16
Height:	(cm) 5.4
Cutout shape:	
Weight:	8.1
Glow Wire Test:	850 °

**LAMPS NOT INCLUDED**

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

**Dimensions****LAMP****ELECTRICAL**

Starter:	Electronic Dimmable DALI Integrated
Voltage:	220V-240V

## ACCESSORIES

---



INTERACTIVE-DALI kit  
Ø86mm, white, recessed.  
Can be connected to a  
max. 11 DALI dimmable  
units. Is operated through  
INTERACTIVE-DALI remote  
control or external push  
button. M074030



INTERACTIVE-DALI remote  
control. M104900