

PRODUCT DATA SHEET

Megan System module 1173mm, T16 2x28W - White



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Steel

DESCRIPTION :

Direct-indirect modular system using 2x28 to 2x54W T16 fluorescent lamps. Micro-perforated steel body with a white or grey paint finish, and opaline polycarbonate diffuser foil. Can be installed as a pendant or wall light. Light emission is in compliance with EN12464-1. Light distribution: 84% indirect and 16% direct. Electronic ballast, or Dali-Switchdim dimmable electronic ballast, or INTERACTIVE-DALI system combining a movement detector and a daylight sensor for auto-regulation in relation to people presence and variations in daylight. Intermodule electromechanical connection via cable-free quick connectors. 5-cable through-wiring suitable for 2 or 3 switches circuits (the dimmable version has one switch only). Continuous linear mounting or with 90° connectors, 3 and 4 ways connectors. Dust protection cover made of extruded polycarbonate. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

Light emission



Indirect/direct Diffused



TECHNICAL DATA SHEET

Features

Product name:	Megan System module 1173mm, T16 2x28W - White
Article Code:	L685720
Colour:	White
Material:	Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Office

OPTICS

Emission:	Indirect/direct Diffused
-----------	--------------------------


DIMENSIONS

Length:	(cm) 117
Width:	(cm) 19.6
Height:	(cm) 5.4
Cutout shape:	
Weight:	2.9

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	28
Socket:	G5
Type:	FDH-28
Luminous Flux (lm):	2600
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Dimensions



LAMP



ELECTRICAL

Starter:	Electronic
Voltage:	220V-240V

ACCESSORIES



Steel suspension cable. Height adjustment via integral griplock system in the base plate, max.1900mm. White. L689720



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 3 wires (3x0,75mm²). White. L689920



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 5 wires (5x1,5mm²). White. L689820



Left wall fixing. Ø106mm. Protrusion 50mm. White. L687320



Mid wall fixing. Ø106mm. Protrusion 50mm. White. L687120



Right wall fixing. Ø106mm. Protrusion 50mm. White. L687220



Wall feed 3 wires (3x0,75mm²). For dimmable version: 2 pieces required. L687000



End cap. Overall thickness 8mm. Useful thickness 3mm. White. L689020



Linear connector. Overall thickness 8mm. Useful thickness 3mm. White. L689120



L-connector. 205x205mm. Internal peg (for external neutral). White. L689220



L-connector. 205x205mm. External peg (for internal neutral). White. L689320



T-connector. 205x205mm. Peg on the left (for neutral on the right). White. L689420



T-connector. 205x205mm. Peg on the right (for neutral on the left). White. L689520



X-connector. 205x205mm. White. L689620