

PRODUCT DATA SHEET

Megan System module 1173mm, T16 2x28-54W - Interactive-Dali - Grey



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Steel

DESCRIPTION :

Direct-indirect modular system using 2x28 to 2x54W T16 fluorescent lamps. Micro-perforated steel body with a white or grey paint finish, and opaline polycarbonate diffuser foil. Can be installed as a pendant or wall light. Light emission is in compliance with EN12464-1. Light distribution: 84% indirect and 16% direct. Electronic ballast, or Dali-Switchdim dimmable electronic ballast, or INTERACTIVE-DALI system combining a movement detector and a daylight sensor for auto-regulation in relation to people presence and variations in daylight. Intermodule electromechanical connection via cable-free quick connectors. 5-cable through-wiring suitable for 2 or 3 switches circuits (the dimmable version has one switch only). Continuous linear mounting or with 90° connectors, 3 and 4 ways connectors. Dust protection cover made of extruded polycarbonate. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

Light emission



Indirect/direct Diffused



TECHNICAL DATA SHEET

Features

Product name:	Megan System module 1173mm, T16 2x28-54W - Interactive-Dali - Grey
Article Code:	L686206
Colour:	Grey
Material:	Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Office

OPTICS

Emission:	Indirect/direct Diffused
-----------	--------------------------


DIMENSIONS

Length:	(cm) 117
Width:	(cm) 19.6
Height:	(cm) 5.4
Cutout shape:	
Weight:	3

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Dimensions



LAMP



ELECTRICAL

Starter:	Interactive-Dali
Voltage:	220V-240V

ACCESSORIES



Steel suspension cable. Height adjustment via integral griplock system in the base plate, max.1900mm. Grey. L689700



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 3 wires (3x0,75mm²). Grey. L689900



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 5 wires (5x1,5mm²). Grey. L689800



Left wall fixing. Ø106mm. Protrusion 50mm. Grey. L687300



Mid wall fixing. Ø106mm. Protrusion 50mm. Grey. L687100



Right wall fixing. Ø106mm. Protrusion 50mm. Grey. L687200



Wall feed 3 wires (3x0,75mm²). For dimmable version: 2 pieces required. L687000



End cap. Overall thickness 8mm. Useful thickness 3mm. Grey. L689000



Linear connector. Overall thickness 8mm. Useful thickness 3mm. Grey. L689100



L-connector. 205x205mm. Internal peg (for external neutral). Grey. L689200



L-connector. 205x205mm. External peg (for internal neutral). Grey. L689300



T-connector. 205x205mm. Peg on the left (for neutral on the right). Grey. L689400



T-connector. 205x205mm. Peg on the right (for neutral on the left). Grey. L689500



X-connector. 205x205mm. Grey. L689600



INTERACTIVE-DALI remote control. M104900



INTERACTIVE-DALI kit Ø86mm, white, recessed. Can be connected to a max. 11 DALI dimmable units. Is operated through INTERACTIVE-DALI remote control or external push button. M074030



Extension movement detector white, recessed. To be used when the area to be covered is bigger than 6,00x5,00m by height 2,50m. To be connected to one of the outputs of the INTERACTIVE-DALI controller. No extra mains connection required. M074130