

## PRODUCT DATA SHEET

### Megan System module 1173mm, T16 2x28-54W - Interactive-Dali - White



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Steel

#### DESCRIPTION :

Direct-indirect modular system using 2x28 to 2x54W T16 fluorescent lamps. Micro-perforated steel body with a white or grey paint finish, and opaline polycarbonate diffuser foil. Can be installed as a pendant or wall light. Light emission is in compliance with EN12464-1. Light distribution: 84% indirect and 16% direct. Electronic ballast, or Dali-Switchdim dimmable electronic ballast, or INTERACTIVE-DALI system combining a movement detector and a daylight sensor for auto-regulation in relation to people presence and variations in daylight. Intermodule electromechanical connection via cable-free quick connectors. 5-cable through-wiring suitable for 2 or 3 switches circuits (the dimmable version has one switch only). Continuous linear mounting or with 90° connectors, 3 and 4 ways connectors. Dust protection cover made of extruded polycarbonate. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

Item no. L686226

#### Light emission



Indirect/direct Diffused



## TECHNICAL DATA SHEET

#### Features

Product name:	Megan System module 1173mm, T16 2x28-54W - Interactive-Dali - White
Colour:	White
Material:	Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Office

#### OPTICS

Emission:	Indirect/direct Diffused
-----------	--------------------------


#### DIMENSIONS

Length:	(cm) 117
Width:	(cm) 19.6
Height:	(cm) 5.4
Cutout shape:	
Weight:	3

#### LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

#### Dimensions



#### LAMP



#### ELECTRICAL

Starter:	Interactive-Dali
Voltage:	220V-240V

## ACCESSORIES



Steel suspension cable. Height adjustment via integral griplock system in the base plate, max.1900mm. White. L689720



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 3 wires (3x0,75mm<sup>2</sup>). White. L689920



Steel suspension cable + power feed cable. Height adjustment capacity, max.1900mm. 5 wires (5x1,5mm<sup>2</sup>). White. L689820



Left wall fixing. Ø106mm. Protrusion 50mm. White. L687320



Mid wall fixing. Ø106mm. Protrusion 50mm. White. L687120



Right wall fixing. Ø106mm. Protrusion 50mm. White. L687220



Wall feed 3 wires (3x0,75mm<sup>2</sup>). For dimmable version: 2 pieces required. L687000



End cap. Overall thickness 8mm. Useful thickness 3mm. White. L689020



Linear connector. Overall thickness 8mm. Useful thickness 3mm. White. L689120



L-connector. 205x205mm. Internal peg (for external neutral). White. L689220



L-connector. 205x205mm. External peg (for internal neutral). White. L689320



T-connector. 205x205mm. Peg on the left (for neutral on the right). White. L689420



T-connector. 205x205mm. Peg on the right (for neutral on the left). White. L689520



X-connector. 205x205mm. White. L689620



INTERACTIVE-DALI remote control. M104900



INTERACTIVE-DALI kit Ø86mm, white, recessed. Can be connected to a max. 11 DALI dimmable units. Is operated through INTERACTIVE-DALI remote control or external push button. M074030



Extension movement detector white, recessed. To be used when the area to be covered is bigger than 6,00x5,00m by height 2,50m. To be connected to one of the outputs of the INTERACTIVE-DALI controller. No extra mains connection required. M074130