

PRODUCT DATA SHEET

Ermes 155 HIT 150W 2x16° - Base plate - Metal grey



DESIGN BY :

Michel Tortel

MATERIALS :

Aluminium

DESCRIPTION :

A range of directional spotlights using 12V halogen and metal halide lamps. 2 options available: with three-phase track adapter, and with base plate. Aluminium body comprised of an optical and power supply unit. Optical unit available in 2 diameter options depending on the light source: ø78mm and ø155mm. Tilt angle of up to 90°, rotation of up to 355°. Electronic transformer. Ferromagnetic ballast. Safety glass with HIT version. Wide range of accessories. Complies with standard EN60598-1 and other specific standards.

Light emission

Accent Lighting

IP20  

TECHNICAL DATA SHEET

Features

| | |
|----------------|--|
| Product name: | Ermes 155 HIT 150W 2x16° - Base plate - Metal grey |
| Article Code: | M059461 |
| Colour: | Metal grey |
| Material: | Aluminium |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

OPTICS

| | |
|-----------|-----------------|
| Emission: | Accent Lighting |
|-----------|-----------------|


DIMENSIONS

| | |
|-----------------|-----------|
| Length: | (cm) 34.6 |
| Height: | (cm) 21.2 |
| Cutout width: | (cm) 15.5 |
| Inclination: | 90 |
| Rotation: | 355 |
| Cutout shape: | |
| Weight: | 4.8 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|-----------|
| Category: | HQI |
| Number: | 1 |
| Lbs: | HIT-CE |
| Watt: | 150 |
| Socket: | G12 |
| Type: | MT/UB-150 |
| Luminous Flux (lm): | 14000 |
| Colour Rendering: | 80-85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 10000 |

Dimensions



LAMP

IP20  

ELECTRICAL

| | |
|----------|-----------|
| Voltage: | 220V-240V |
|----------|-----------|

ACCESSORIES



ERMES155 - Anti-dazzle
ring. Ø155mm. Black.
M081157



ERMES155 - Wall washer
screen. Ø155mm. Black.
M081167



ERMES155 - Filter-holder +
sanded glass filter.
Ø140mm. M086835