

PRODUCT DATA SHEET

L.D. System 66 - QR-CBC max20W - Nickel matt



DESIGN BY :

Alberto Meda , Paolo Rizzatto

MATERIALS :

Die-cast aluminium, Steel

DESCRIPTION :

A range of recessed fixed downlights using 12V halogen, metal-halide or fluorescent lamps. Die-cast aluminium and steel body. Reflectors made from super pure aluminium (metallised polycarbonate with fluorescent version). Die-cast aluminium ring, available in 3 colours, to be clipped on the fixture. 4 diameter options: ø66mm, ø96mm, ø156mm or Ø206mm. UV filter included with HIT version. Control gear to be ordered separately with halogen and HIT versions. Integral electronic ballast with fluorescent version. Complies with standard EN60598-1 and other specific standards.

Light emission



Accent Lighting




TECHNICAL DATA SHEET

Features

Product name:	L.D. System 66 - QR-CBC max20W - Nickel matt
Article Code:	L600670
Colour:	Nickel matt
Material:	Die-cast aluminium, Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Hospitality Restaurant, Retail, Private Residence

Dimensions



OPTICS

Emission:	Accent Lighting
-----------	-----------------

DIMENSIONS

Height:	(cm) 4.7
Cutout width:	(cm) 6.6
Cutout diameter:	(cm) 5.8
Cutout shape:	Rounded
Weight:	0.6
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	QR-CBC35
Watt:	20
Socket:	GU4
Type:	HRGS-35-GU4-20
ILCOS:	HRGS
Colour Rendering:	100
Colour temperature (K):	3000
Duration (h):	4000


LAMP



ELECTRICAL

Trasformer availability:	Remote
Voltage:	12V

ACCESSORIES



Recessing box for concrete ceilings with cut-out Ø58mm L621000



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211