

## PRODUCT DATA SHEET

### L.D. System 96 - QT12 max50W - Chrome



#### DESIGN BY :

Alberto Meda , Paolo Rizzatto

#### MATERIALS :

Die-cast aluminium, Steel

#### DESCRIPTION :

A range of recessed fixed downlights using 12V halogen, metal-halide or fluorescent lamps. Die-cast aluminium and steel body. Reflectors made from super pure aluminium (metallised polycarbonate with fluorescent version). Die-cast aluminium ring, available in 3 colours, to be clipped on the fixture. 4 diameter options: ø66mm, ø96mm, ø156mm or Ø206mm. UV filter included with HIT version. Control gear to be ordered separately with halogen and HIT versions. Integral electronic ballast with fluorescent version. Complies with standard EN60598-1 and other specific standards.

#### Light emission



Accent Lighting




### TECHNICAL DATA SHEET

#### Features

Product name:	L.D. System 96 - QT12 max50W - Chrome
Article Code:	L600390
Colour:	Chrome
Material:	Die-cast aluminium, Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Hospitality Restaurant, Retail, Private Residence

#### Dimensions



#### OPTICS

Emission:	Accent Lighting
-----------	-----------------

#### DIMENSIONS

Height:	(cm) 6.6
Cutout width:	(cm) 9.6
Cutout diameter:	(cm) 8.1
Cutout shape:	Rounded
Weight:	1.2
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	QT12-UVrax
Watt:	50
Socket:	GY6.35
ILCOS:	HSGST/UB
Luminous Flux (lm):	1180
Colour Rendering:	100
Colour temperature (K):	3000
Duration (h):	4000

#### LAMP



#### ELECTRICAL


Trasformer availability:	Remote
Voltage:	12V

## ACCESSORIES

---



Electronic transformer  
230-240V/12V. Class II.  
Dimmable by trailing or  
leading edge external  
dimmers. 10-60W.  
123x32x23mm. M070211



Recessing box for  
concrete ceilings with cut-  
out Ø81mm. L621001