PRODUCT DATA SHEET

L.D. System 96 - QR-CBC51 max50W - Chrome



DESIGN BY :

Alberto Meda , Paolo Rizzatto

MATERIALS :

Die-cast aluminium, Steel

DESCRIPTION :

A range of recessed fixed downlights using 12V halogen, metal-halide or fluorescent lamps. Diecast aluminium and steel body. Reflectors made from super pure aluminium (metallised polycarbonate with fluorescent version). Die-cast aluminium ring, available in 3 colours, to be clipped on the fixture.4 diameter options: Ø66mm, Ø966mm, Ø156mm or Ø206mm. UV filter included with HIT version. Control gear to be ordered separately with halogen and HIT versions. Integral electronic ballast with fluorescent version. Complies with standard EN60598-1 and other specific standards.

Light emission



IP20 🛈 🚳

Accent Lighting

TECHNICAL DATA SHEET

Features

Colour:

Material: Series:

Product name: Article Code:

Environment:

Area contract:

L.D. System 96 - QR-CBC51 max50W - Chrome L600490 Chrome Die-cast aluminium, Steel Architectural Indoor Hospitality Hotel, Hospitality Restaurant, Retail, Private Residence

Accent Lighting

OPTICS

Emission:

DIMENSIONS

Height:	(cm) 5.2
Cutout width:	(cm) 9.6
Cutout diameter:	(cm) 8.1
Cutout shape:	Rounded
Weight:	1.2
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	Qr-cb 51
Watt:	50
Socket:	Gu5.3
Туре:	N/s
Colour Rendering:	1a
Colour temperature (K):	N/s

Dimensions



LAMP IP20 🕸 🌃

ELECTRICAL

Trasformer availability: Voltage: Remote 12V

Artemide

ACCESSORIES



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211



Ø245 Recessing box for concrete ceiilngs with cutout Ø81mm. L621001