

PRODUCT DATA SHEET

LD System 206 - HIT-CE max150W - Nickel matt



DESIGN BY :

Alberto Meda , Paolo Rizzatto

MATERIALS :

Die-cast aluminium, Steel

DESCRIPTION :

A range of recessed fixed downlights using 12V halogen, metal-halide or fluorescent lamps. Die-cast aluminium and steel body. Reflectors made from super pure aluminium (metallised polycarbonate with fluorescent version). Die-cast aluminium ring, available in 3 colours, to be clipped on the fixture. 4 diameter options: $\varnothing 66\text{mm}$, $\varnothing 96\text{mm}$, $\varnothing 156\text{mm}$ or $\varnothing 206\text{mm}$. UV filter included with HIT version. Control gear to be ordered separately with halogen and HIT versions. Integral electronic ballast with fluorescent version. Complies with standard EN60598-1 and other specific standards.

Light emission



Accent Lighting


IP20    

TECHNICAL DATA SHEET

Features

Product name:	LD System 206 - HIT-CE max150W - Nickel matt
Article Code:	L603670
Colour:	Nickel matt
Material:	Die-cast aluminium, Steel
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Hospitality Restaurant, Retail, Private Residence

Dimensions



OPTICS

Emission:	Accent Lighting
-----------	-----------------

DIMENSIONS

Height:	(cm) 20
Cutout width:	(cm) 20.6
Cutout diameter:	(cm) 17.6
Cutout shape:	Rounded
Weight:	1.7
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-CE
Watt:	150
Socket:	G12
Type:	MT/UB-150
Luminous Flux (lm):	14000
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	10000

LAMP

IP20    

ELECTRICAL

Starter:	Electronic Remote
Voltage:	230/240V



Electronic ballast 230-
240V, Class I, For HIT
1x150W, 150x90x40mm.
M070622