

## PRODUCT DATA SHEET

### Ourea Recessed 156 - LED 33W 4000K FL



**DESIGN BY :**

Artemide

**MATERIALS :**

Aluminium

**DESCRIPTION :**

A range of recessed downlights available in size  $\varnothing 156$  using high-performing LED, metal-halide, fluorescent and 12V halogen lamps. The fixture consists of a frame to be fixed and plastered onto the plasterboard false ceiling and an aluminium body. LED version with monochromatic warm white (3000k) and neutral white (4000k) emission. Super pure aluminium optics and protection glass with HIT version. Fluorescent version comes with a prism optic diffuser, electronic control gear. Electronic power supply to be ordered separately with LED, HIT and halogen version. Complies with EN60598-1 and other specific standards.

M177820FL

Aluminium reflector FL: Flood (2x15 ° < angle  $\approx 20^\circ$ ).

**Light emission**

Direct

IP20  

#### TECHNICAL DATA SHEET

**Features**

|               |                                       |
|---------------|---------------------------------------|
| Product name: | Ourea Recessed 156 - LED 33W 4000K FL |
| Colour:       | White                                 |
| Material:     | Aluminium                             |
| Series:       | Architectural                         |
| Environment:  | Indoor                                |

**OPTICS**

|           |        |
|-----------|--------|
| Emission: | Direct |
|-----------|--------|

**DIMENSIONS**

|                 |           |
|-----------------|-----------|
| Cutout width:   | (cm) 15.6 |
| Cutout shape:   | Rounded   |
| Weight:         | 2         |
| Glow Wire Test: | 960 °     |

**LAMPS INCLUDED**

|                        |      |
|------------------------|------|
| Category:              | LED  |
| Watt:                  | 33   |
| Typology:              | 1    |
| Color Rendering:       | N/s  |
| Color temperature (K): | 4000 |

**LAMP**

IP20  

**ELECTRICAL**

|          |          |
|----------|----------|
| Voltage: | 220-240V |
|----------|----------|

## ACCESSORIES



LED POWER FEED 14-50W  
NON DIMMABLE M074530



LED POWER FEED 14-50W  
DIMMABLE  
DALI/SWITCHDIM/PHASE  
CUT M074531