# **Artemide**

# PRODUCT DATA SHEET

# **Toplite Square Adjustable - White**



#### **DESIGN BY :**

Artemide

#### MATERIALS :

Die-cast Aluminium

# **DESCRIPTION**:

A range of recessed downlights, fixed or adjustable, round or square, using 12V dichroic halogen lamps, HIPAR51 metal halide and 230-240V leds. Body in die-cast aluminium or steel, available in different colours. Multiple size options: ø88mm, ø100mm, ø125mm, ø158mm, 88x88mm and 95x95mm. Tilt angle of up to 70°, rotation of up to 355° depending on the version. Lamp holding ring made from aluminium, thermoplastic material or with coloured glass. Lamps can be maintained without the need for tools by a simple quarter turn rotation. Version IP44 comes with integral safety cover and sealed glass. Remote transformer. Complies with standard EN60598-1 and other specific standards.

# Light emission

Accent Lighting



# **TECHNICAL DATA SHEET**

# Features

Product name: Article Code: Colour: Material: Series: Environment: Area contract: Toplite Square Adjustable - White M041205 White Die-cast Aluminium Architectural Indoor

Accent Lighting

OPTICS Emission:

# DIMENSIONS

| Length:         | (cm) 9.5 |
|-----------------|----------|
| Width:          | (cm) 9.5 |
| Cutout length:  | (cm) 8.3 |
| Cutout Width:   | (cm) 8.3 |
| Recessed depth: | (cm) 13  |
| Inclination:    | 30       |
| Cutout shape:   | Squared  |
| Weight:         | 0.2      |
| Glow Wire Test: | 960 °    |

# LAMPS NOT INCLUDED

| Category:               | HALO    |
|-------------------------|---------|
| Number:                 | 1       |
| Lbs:                    | QR-CBC5 |
| Watt:                   | 50      |
| Socket:                 | GU5.3   |
| Туре:                   | HRGS/UB |
| Colour Rendering:       | 100     |
| Colour temperature (K): | 3000    |
|                         |         |

#### Dimensions



LAMP IP20 ⊕ √

# ELECTRICAL

Trasformer availability: Voltage: Remote 12V



ACCESSORIES



TOPLITE - Louvre M081047



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211