

PRODUCT DATA SHEET

Toplite 88 Fix Low Luminance - HIPAR51 - White



DESIGN BY :

Artemide

MATERIALS :

Die-cast Aluminium

DESCRIPTION :

A range of recessed downlights, fixed or adjustable, round or square, using 12V dichroic halogen lamps, HIPAR51 metal halide and 230-240V leds. Body in die-cast aluminium or steel, available in different colours. Multiple size options: ø88mm, ø100mm, ø125mm, ø158mm, 88x88mm and 95x95mm. Tilt angle of up to 70°, rotation of up to 355° depending on the version. Lamp holding ring made from aluminium, thermoplastic material or with coloured glass. Lamps can be maintained without the need for tools by a simple quarter turn rotation. Version IP44 comes with integral safety cover and sealed glass. Remote transformer. Complies with standard EN60598-1 and other specific standards.

Light emission

Accent Lighting

IP20  

TECHNICAL DATA SHEET

Features

Product name:	Toplite 88 Fix Low Luminance - HIPAR51 - White
Article Code:	M046200
Colour:	White
Material:	Die-cast Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

OPTICS

Emission:	Accent Lighting
-----------	-----------------


DIMENSIONS

Cutout width:	(cm) 8.8
Cutout diameter:	(cm) 7.5
Recessed depth:	(cm) 13
Cutout shape:	Rounded
Weight:	0.1
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIPAR51
Watt:	35
Socket:	GX10
Type:	MRS/UB-35
Colour Rendering:	80-85
Colour temperature (K):	3000

Dimensions



LAMP

IP20  

ELECTRICAL

Trasformer availability:	Remote
Voltage:	220V-240V

ACCESSORIES



ELECTRONIC BALLAST-
UNIT "SLIM" FOR HIT 35W.
Dim. 150x62x30mm.
M070032