

PRODUCT DATA SHEET

Toplite 100 Bi-Adjustable HALO - White



DESIGN BY :

Artemide

MATERIALS :

Die-cast Aluminium

DESCRIPTION :

A range of recessed downlights, fixed or adjustable, round or square, using 12V dichroic halogen lamps, HIPAR51 metal halide and 230-240V leds. Body in die-cast aluminium or steel, available in different colours. Multiple size options: ø88mm, ø100mm, ø125mm, ø158mm, 88x88mm and 95x95mm. Tilt angle of up to 70°, rotation of up to 355° depending on the version. Lamp holding ring made from aluminium, thermoplastic material or with coloured glass. Lamps can be maintained without the need for tools by a simple quarter turn rotation. Version IP44 comes with integral safety cover and sealed glass. Remote transformer. Complies with standard EN60598-1 and other specific standards.

Light emission

Accent Lighting


IP20  

TECHNICAL DATA SHEET

Features

Product name:	Toplite 100 Bi-Adjustable HALO - White
Article Code:	M042905
Colour:	White
Material:	Die-cast Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions



OPTICS

Emission:	Accent Lighting
-----------	-----------------

DIMENSIONS

Cutout width:	(cm) 10
Cutout diameter:	(cm) 8.8
Recessed depth:	(cm) 13
Inclination:	30
Rotation:	355
Cutout shape:	Rounded
Weight:	0.2
Glow Wire Test:	960 °

LAMP

IP20  

ELECTRICAL

Trasformer availability:	Remote
Voltage:	12V

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	QR-CBC51
Watt:	50
Socket:	GU5.3
Type:	HRGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

ACCESSORIES



Electronic transformer
230-240V/12V. Class II.
Dimmable by trailing or
leading edge external
dimmers. 10-60W.
123x32x23mm. M070211



TOPLITE - Louvre
M081047