PRODUCT DATA SHEET

Toplite 100 Bi-Adjustable HALO - Metal Grey



DESIGN BY :

Artemide

MATERIALS :

Die-cast Aluminium

DESCRIPTION:

A range of recessed downlights, fixed or adjustable, round or square, using 12V dichroic halogen lamps, HIPAR51 metal halide and 230-240V leds. Body in die-cast aluminium or steel, available in different colours. Multiple size options: ø88mm, ø100mm, ø125mm, ø158mm, 88x88mm and 95x95mm. Tilt angle of up to 70°, rotation of up to 355° depending on the version. Lamp holding ring made from aluminium, thermoplastic material or with coloured glass. Lamps can be maintained without the need for tools by a simple quarter turn rotation. Version IP44 comes with integral safety cover and sealed glass. Remote transformer. Complies with standard EN60598-1 and other specific standards.

Light emission

Accent Lighting



TECHNICAL DATA SHEET

Features

Colour:

Material:

Series:

Product name: Article Code:

Environment:

Area contract:

Toplite 100 Bi-Adjustable HALO -Metal Grey M042965 Metal Grey Die-cast Aluminium Architectural Indoor

Accent Lighting

OPTICS

Emission:

DIMENSIONS

 Cutout width:
 (cm) 10

 Cutout diameter:
 (cm) 8.8

 Recessed depth:
 (cm) 13

 Inclination:
 30

 Rotation:
 355

 Cutout shape:
 Rounded

 Weight:
 0.2

 Glow Wire Test:
 960 °

LAMPS NOT INCLUDED

0-1	
Category:	HALO
Number:	1
Lbs:	QR-CBC5
Watt:	50
Socket:	GU5.3
Туре:	HRGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

Dimensions



LAMP IP20 ⊕ √

ELECTRICAL

Trasformer availability: Voltage:

Remote 12V



ACCESSORIES



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211



TOPLITE - Louvre M081047