

PRODUCT DATA SHEET

Bolero 625x625mm - Dimmable Dali

**DESIGN BY :**

Artemide

MATERIALS :

Painted Steel

DESCRIPTION :

Recessed luminaire for 2x55W TC-L fluorescent lamps. Main reflector in steel with a white paint finish. Polished aluminium screen equipped with a "PRISMOPTIC" polycarbonate diffuser. For installation into false ceiling systems with 600x600mm and 625x625mm modules, or into plasterboard false ceilings using a special recessing frame (optional). Lamps can be maintained without the use of tools. Complies with standard EN60598-1 and other specific standards.

Light emission

Soft Light



TECHNICAL DATA SHEET

Features

| | |
|----------------|----------------------------------|
| Product name: | Bolero 625x625mm - Dimmable Dali |
| Article Code: | M162421 |
| Colour: | White |
| Material: | Painted Steel |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

OPTICS


| | |
|-----------|------------|
| Emission: | Soft Light |
|-----------|------------|

DIMENSIONS

| | |
|-----------------|-----------|
| Length: | (cm) 62.1 |
| Width: | (cm) 62.1 |
| Height: | (cm) 11.2 |
| Recessed depth: | (cm) 31 |
| Cutout shape: | |
| Weight: | 7.3 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 2 |
| Lbs: | TC-LEL |
| Watt: | 55 |
| Socket: | 2G11 |
| Type: | FSDH |
| Luminous Flux (lm): | 4800 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 12000 |

Dimensions**LAMP****ELECTRICAL**

| | |
|----------|-------------------------------------|
| Starter: | Electronic Dimmable Dali Integrated |
| Voltage: | 220V-240V |

ACCESSORIES



Recess frame for
installation on
plasterboard false ceiling.
625x625mm. M160602