

## PRODUCT DATA SHEET

### Nothing Recessed Round Ø155 Adjustable - HIT 20/35/70W 2x20°



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Die-cast Aluminium

#### DESCRIPTION :

Adjustable downlight ø155mm using HIT G8,5 light source. Recessing ring made from aluminium. Tilt angle of up to 32°. Remote control gear. Optional white ring in injection moulded plastic for an installation without plaster finish coat (fitting by one quarter turn rotation). Safety glass included. Complies with standard en60598-1 and other specific standard.

Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, NOTHING RECESSED is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

#### Light emission

Direct Adjustable




### TECHNICAL DATA SHEET

#### Features

Product name:	Nothing Recessed Round Ø155 Adjustable - HIT 20/35/70W 2x20°
Article Code:	M063220
Colour:	N/s
Material:	Die-cast Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Retail, Office, Private Residence

#### Dimensions



#### OPTICS

Emission:	Direct Adjustable
-----------	-------------------

#### DIMENSIONS

Width:	(cm) 21
Height:	(cm) 32
Cutout width:	(cm) 15.5
Cutout diameter:	(cm) 18.6
Recessed depth:	(cm) 32
Inclination:	32
Cutout shape:	Rounded
Weight:	1.3
Glow Wire Test:	960 °

#### LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-TC-CE
Watt:	70
Socket:	G8.5
Type:	MT/UB-70
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	12000

#### LAMP



#### ELECTRICAL

Starter:	Electronic Remote
Voltage:	220V-240V

## ACCESSORIES

---



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522



NOTHING RECESSED ROUND Ø155 - Ring in injection moulded plastic. Ø215mm. White finish. M065000



UV filter for HIT version M080085