PRODUCT DATA SHEET

Nothing Recessed Round Ø155 Adjustable - HIT 70W 2x20°



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Die-cast Aluminium

DESCRIPTION :

Adjustable downlight #155mm using HIT G12 light source. Recessing ring made from aluminium. Tilt angle of up to 32°. Remote control gear. Optional white ring in injection moulded plastic for an installation without plaster finish coat (fitting by one quarter turn rotation). Safety glass included. Complies with standard en60598-1 and other specific standard.

Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, NOTHING RECESSED is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

Light emission

Direct Adjustable



Features

Product name:

Article Code: Colour: Material: Series: Environment: Area contract: Nothing Recessed Round Ø155 Adjustable - HIT 70W 2x20° M063620 N/s Die-cast Aluminium Architectural Indoor Hospitality Hotel, Retail, Office, Private Residence

Dimensions



Direct Adjustable

DIMENSIONS

OPTICS Emission:

Width:	(cm) 21
Height:	(cm) 32
Cutout width:	(cm) 15.5
Cutout diameter:	(cm) 18.6
Recessed depth:	(cm) 32
Inclination:	32
Cutout shape:	Rounded
Weight:	1.3
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-CE
Watt:	70
Socket:	G12
Туре:	MT/UB-70
Luminous Flux (Im):	6600
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	12000

LAMP IP20 ⓓ ☞

ELECTRICAL

Starter: Voltage: Electronic Remote 220V-240V

Artemide

ACCESSORIES



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522



NOTHING RECESSED ROUND Ø155 - Ring in injection moulded plastic. Ø215mm. White finish. M065000



UV filter for HIT version M080085