

# PRODUCT DATA SHEET

# Nothing Recessed Rectangular - 3 Lamps - QR111



#### **DESIGN BY:**

Ernesto Gismondi

#### **MATERIALS:**

Extruded Aluminium

#### **DESCRIPTION:**

Adjustable downlight using QR111 12V halogen lamps recessing frame made from aluminium. Each spotlight may be adjusted individually with a tilt angle ranging from -20° to +70°, and rotation of up to 355°. Remote transformer. Complies with standard EN60598-1 and other specific standard. Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, NOTHING RECESSED is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

## Light emission

Direct Adjustable



-0-

## **TECHNICAL DATA SHEET**

#### **Features**

Nothing Recessed Rectangular - 3 Lamps - QR111 Product name:

Article Code: M069225 Colour: N/s

Extruded Aluminium Material: Series: Architectural

Environment: Indoor

Area contract: Hospitality Hotel, Retail, Office

## **OPTICS**

Emission: Direct Adjustable


## **DIMENSIONS**

Length: (cm) 38.8 (cm) 13.8 Width: Height: (cm) 21 **Cutout length:** (cm) 17 **Cutout Width:** (cm) 42 Recessed depth: (cm) 20 Inclination: -20/+70 Rotation: 355 Weight: 21 Glow Wire Test: 960 9

## LAMPS NOT INCLUDED

Category: HALO Number: QR111 Lbs: Watt: 100 Socket: G53 Type: HMGS/UB Colour Rendering: 100 Colour temperature (K): 3000 3000 Duration (h):

## **Dimensions**



## LAMP





#### **ELECTRICAL**

Trasformer availability: Remote Voltage: 12V

# Artemide

## **ACCESSORIES**



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-105W. 102x51x30mm. M070412



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-150W. 189x38x34mm. M072111