

PRODUCT DATA SHEET

Nothing Recessed Rectangular - 3 Lamps - 2xQR111 + 1xHIR111



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

Adjustable downlight using QR111 12V halogen lamps + HIR111 metal halide lamp. Recessing frame made from aluminium. Each spotlight may be adjusted individually with a tilt angle ranging from -20° to +70°, and rotation of up to 355°. Remote transformer. Complies with standard EN60598-1 and other specific standard.

Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, NOTHING RECESSED is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

Light emission

Direct Adjustable



TECHNICAL DATA SHEET

Features

Product name:	Nothing Recessed Rectangular - 3 Lamps - 2xQR111 + 1xHIR111
Article Code:	M069525
Colour:	N/s
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Retail, Office

OPTICS

Emission:	Direct Adjustable
-----------	-------------------

DIMENSIONS


Length:	(cm) 38.8
Width:	(cm) 13.8
Height:	(cm) 21
Cutout length:	(cm) 17
Cutout Width:	(cm) 42
Recessed depth:	(cm) 20
Inclination:	-20/+70
Rotation:	355
Weight:	2.1
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	HALO
Number:	2
Lbs:	QR111
Watt:	100
Socket:	G53
Type:	HMG5/UB
Colour Rendering:	100
Colour temperature (K):	3000
Duration (h):	3000

Category:	HQI
Number:	1
Lbs:	HIR111
Watt:	70
Socket:	GX8.5
Type:	MRS/UB-70
Colour Rendering:	80-85
Colour temperature (K):	3000

Dimensions



LAMP



ELECTRICAL

Starter:	Remote
Trasformer availability:	Remote

ACCESSORIES



Electronic transformer
230-240V/12V. Class II.
Dimmable by trailing or
leading edge external
dimmers. 10-60W.
123x32x23mm. M070211



Electronic transformer
230-240V/12V. Class II.
Dimmable by trailing or
leading edge external
dimmers. 35-105W.
102x51x30mm. M070412



Electronic transformer
230-240V/12V. Class II.
Dimmable by trailing or
leading edge external
dimmers. 35-150W.
189x38x34mm. M072111



Electronic ballast 230-
240V. Class I. For HIT
1x35W. 155x83x32mm.
M070322



Electronic ballast 230-
240V. Class I. For HIT
2x35W. 180x80x34mm.
M070422



Electronic ballast 230-
240V. Class I. For HIT
1x70W. 150x80x35mm.
M070522