

PRODUCT DATA SHEET

Nothing Recessed Rectangular - 3 Lamps - 1xQR111 + 2xHIR111



DESIGN BY:

Ernesto Gismondi

MATERIALS:

Extruded Aluminium

DESCRIPTION:

Adjustable downlight using QR111 12V halogen lamp + HIR111 metal halide lamps. Recessing frame made from aluminium. Each spotlight may be adjusted individually with a tilt angle ranging from -20° to +70°, and rotation of up to 355°. Remote transformer. Complies with standard EN60598-1 and other specific standard.

Created with the purpose of making the lighting fixture disappear completely into the false ceiling as to solely draw attention to the lighting effects, NOTHING RECESSED is a complete range of recessed luminaires, whose installation requires a finish coat of plaster.

Light emission

Direct Adjustable





TECHNICAL DATA SHEET

Features

Product name: Nothing Recessed Rectangular - 3 Lamps - 1xQR111 + 2xHIR111

Article Code: M069625

 Material:
 Extruded Aluminium

 Series:
 Architectural

 Environment:
 Indoor

Area contract: Hospitality Hotel, Retail, Office

OPTICS

Emission: Direct Adjustable

DIMENSIONS

Length: (cm) 38.8 (cm) 13.8 Width: Height: (cm) 21 Cutout length: (cm) 17 **Cutout Width:** (cm) 42 Recessed depth: (cm) 20 Inclination: -20/+70 Rotation: 355 Weight: 2.1 Glow Wire Test: 960°

LAMPS NOT INCLUDED

Category: HALO Number: Lbs: QR111 Watt: 100 Socket: G53 HMGS/UB Type: Colour Rendering: 100 Colour temperature (K): 3000 Duration (h): 3000

 Category:
 HQI

 Number:
 2

 Lbs:
 HIR111

 Watt:
 70


 Socket:
 GX8.5

 Type:
 MRS/UB-70

 Colour Rendering:
 80-85

 Colour temperature (K):
 3000

Dimensions



LAMP





ELECTRICAL

Starter: Remote Trasformer availability: Remote

Artemide

ACCESSORIES



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-105W. 102x51x30mm. M070412



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-150W. 189x38x34mm. M072111



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322



Electronic ballast 230-240V. Class I. For HIT 2x35W. 180x80x34mm. M070422



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522