

## A.24 - Ceiling Sharping Emission - Curved Elements - 24° - R=561mm - α=90° - 2700K - Brushed Silver



IP20   Dimmerable: 


### DESIGN BY

Carlotta de Bevilacqua

### DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented optoelectronic technology.

### TECHNICAL DRAWINGS



### FEATURES

<b>Article Code:</b>	AQ61815	<b>Series:</b>	Indoor, 2018
<b>Colour:</b>	Brushed Silver		Artemide Collection
<b>Installation:</b>	Recessed, Wall, Suspension, Ceiling	<b>Emission:</b>	Direct
<b>Environment:</b>	Indoor		

### DIMENSIONS

<b>Width:</b>	cm 2.7
<b>Height:</b>	cm 5.4

### INCLUDED SOURCES

<b>Category:</b>	LED	<b>Color temperature (K):</b>	2700K
<b>Number:</b>	1	<b>Color Tolerance:</b>	MacAdam 2SDCM
<b>Watt:</b>	12W	<b>Service Life:</b>	L70 (6K) 50000h
<b>Type:</b>	0		

### LUMINAIRE

<b>Watt:</b>	12W	<b>Delivered lumens output (lm):</b>	839lm
		<b>CCT:</b>	2700K
		<b>CRI:</b>	90

### Notes

\*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. Bracket for fixing to ceiling is included: 1 for 1176mm length - 2 for 2352 mm length. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

**ACCESSORIES**



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17901



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17904



240W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000



150W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100




240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



Cap for cable - Brushed Silver AQ35315



A.24 - Flexible Cover L=10m - Black AQ92004



A.24 - Remote Box Power Supply Kit - 313x243x57,5h - (230VAC-48VDC 240W DALI) AQ16000



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - DALI AQ16801



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable AQ17801




240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17301




A.24 - Wall/Ceiling Accessories - End Cap (2x) - Brushed Silver AQ35015




240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17304



A.24 - Wall/Ceiling Accessories - Transition Cap - Brushed silver




A.24 - Louver for Curved Elements - White (Order 1 pc for R=561-60°/90° R=750 45°, 2 pcs



A.24 - Louver for Curved Elements - Black (Order 1 pc for R=561-60°/90° R=750 45°, 2 pcs


AQ39415



A.24 - Flexible  
Cover L=10m -  
White  
AQ92001




A.24 - Insulating  
Spacer (1x) -  
Brushed Silver  
AQ35215



DALI to DALI-Selv  
Interface  
103x67x21H  
AQ18200

for R=750 90°)  
AQ91101



150W Ceiling  
power supply kit -  
321x91x111H -  
230VAC-48VDC  
IP20 - Dimmable  
DALI - White  
AQ17701



A.24 - Flexible  
Cover L=2m -  
White  
AQ92101

for R=750 90°)  
AQ91104



150W Ceiling  
power supply kit -  
321x91x111H -  
230VAC-48VDC  
IP20 - Dimmable  
DALI - Black  
AQ17704



A.24 - Flexible  
Cover L=2m -  
Black  
AQ92104