


A.24 - Ceiling Sharping Emission - Curved Elements - 62° - R=750mm - α=90° - 4000K - Brushed Copper



IP20   Dimmerable: 


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented optoelectronic technology.

TECHNICAL DRAWINGS



FEATURES

Article Code:	AQ63618	Series:	Indoor, 2018
Colour:	Brushed Copper	Emission:	Artemide Collection Direct
Installation:	Recessed, Wall, Suspension, Ceiling		
Environment:	Indoor		

DIMENSIONS

Width:	cm 2.7
Height:	cm 5.4

INCLUDED SOURCES

Category:	LED	Color temperature (K):	4000K
Number:	1	CRI:	90
Watt:	25W		
Type:	0		

LUMINAIRE

Watt:	25W	Delivered lumens output (lm):	1555lm
		CCT:	4000K
		CRI:	80

Notes

*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. Bracket for fixing to ceiling is included: 1 for 1176mm length - 2 for 2352 mm length. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

ACCESSORIES



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17901



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17904



240W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000




150W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100



240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



A.24 - Flexible Cover L=10m - Black AQ92004



A.24 - Remote Box Power Supply Kit - 313x243x57,5h - (230VAC-48VDC 240W DALI) AQ16000



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - DALI AQ16801




240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable AQ17801



240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17301



240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17304



A.24 - Wall/Ceiling Accessories - End Cap (2x) - Brushed Copper AQ35018

A.24 - Louver for Coured Elements - White (Order 1 pc for R=561-60°/90°


R=750 45°, 2 pcs



A.24 - Wall/Ceiling Accessories - Transition Cap - Brushed copper AQ39418

A.24 - Louver for Coured Elements - Black (Order 1 pc for R=561-60°/90°

R=750 45°, 2 pcs




A.24 - Flexible
Cover L=10m -
White
AQ92001

for R=750 90°)
AQ91101



Cap for cable -
Brushed Copper
AQ35318

for R=750 90°)
AQ91104



150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - White
AQ17701



150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - Black
AQ17704




A.24 - Flexible
Cover L=2m -
White
AQ92101



A.24 - Insulating
Spacer (1x) -
Brushed Copper
AQ35218



A.24 - Flexible
Cover L=2m -
Black
AQ92104



DALI to DALI-Selv
Interface
103x67x21H
AQ18200