PRODUCT DATA SHEET PRODUCT CODE: AQ32420

A.24 - Ceiling Sharping Emission - Track - Direct Emission - 1176mm - 24° -2700K - Brushed Bronze




DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented



FEATURES

Colour: Brushed Bronze Artemide Collection Installation: Recessed, Wall, Suspension, Ceiling Indoor DIMENSIONS Length: cm 117.6 cm 2.7 Height: cm 5.4 kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): 2700K Number: 1 Color Tolerance: MacAdam 2SDCM L70 (6K) 50000h Watt: 25W Service Life: L70 (6K) 50000h LUMINAIRE				
Installation: Recessed, Wall, Suspension, Ceiling Indoor DIMENSIONS Length: cm 117.6 width: cm 2.7 Height: cm 5.4 Weight: kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: LT0 (6K) 50000h LUMINAIRE	Article Code:	AQ32420	Series:	Indoor, 2018
Suspension, Ceiling Indoor	Colour:	Brushed Bronze		Artemide Collection
DIMENSIONS Cm 117.6 Cm 2.7 Cm 5.4 Kg 1.4 Color temperature (K): 2700K Color tolerance: MacAdam 2SDCM Color tolerance	Installation:	Recessed, Wall,	Emission:	Direct
DIMENSIONS Cm 117.6 Cm 2.7 Height:		Suspension, Ceiling		
Length: cm 117.6 Width: cm 2.7 Height: cm 5.4 Weight: kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): 2700K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: L70 (6K) 50000h Type: 0	Environment:	Indoor		
Length: cm 117.6 Width: cm 2.7 Height: cm 5.4 Weight: kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): 2700K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: L70 (6K) 50000h Type: 0	DIMENSIONS			
Width: cm 2.7 Height: cm 5.4 Weight: kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): 2700K MacAdam 2SDCM Matt: 25W Service Life: L70 (6K) 50000h Type: 0		cm 117.6		
Height:	_			
Weight: kg 1.4 INCLUDED SOURCES Category: LED Color temperature (K): 2700K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: L70 (6K) 50000h Type: 0				
NCLUDED SOURCES	•			
Category: LED Color temperature (K): 2700K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: L70 (6K) 50000h Type: 0	Weight:	kg 1.4		
Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 25W Service Life: L70 (6K) 50000h Type: 0	INCLUDED SOURCES			
Watt: 25W Service Life: L70 (6K) 50000h Type: 0	Category:	LED	Color temperature (K):	2700K
Type: 0 LUMINAIRE	Number:	1	Color Tolerance:	MacAdam 2SDCM
Type: 0 LUMINAIRE	Watt:	25W	Service Life:	L70 (6K) 50000h
LUMINAIRE	Type:	0		, , , , , , , , , , , , , , , , , , , ,
	71			
Watt: 22W Delivered lumens output (lm): 1528lm	LUMINAIRE			
	Watt:	22W	Delivered lumens output (lm): 1528lm

Notes

*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. Bracket for fixing to ceiling is included: 1 for 1176mm length - 2 for 2352 mm length. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

CCT:

CRI:

2700K

90



ACCESSORIES



A.24 - Wall/Ceiling Accessories - End Cap (2x) - Brushed Bronze AQ35020



240W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17901



150W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17904



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 -Undimmable AQ17801



A.24 - Wall/Ceiling Accessories -Transition Cap -Brushed bronze AQ39420



150W Ceiling power supply kit -321x91x111H -



A.24 - Remote Box Power Supply Kit -313x243x57,5h -(230VAC-48VDC 240W DALI) AQ16000



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17301



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 - DALI AQ16801



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17304



Cap for cable -Brushed Bronze AQ35320



150W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - Black AQ17704



230VAC-48VDC IP20 - Dimmable DALI - White AQ17701

DALI to DALI-Selv Interface 103x67x21H AQ18200



A.24 - Insulating Spacer (1x) -Brushed Bronze AQ35220



A.24 - Sharping Kit L=1176mm -White AQ26001



A.24 - Sharping Kit L=1176mm - Black AQ26004