

A.24 - Recessed Diffused Emission - Curved Elements - R=750mm - $\alpha=45^\circ$ - 3000K




IP20 Dimmerable:

DESIGN BY

Carlotta de Bevilacqua

TECHNICAL DRAWINGS



FEATURES

Article Code:	AQ52101	Series:	Indoor, 2018 Artemide Collection
Colour:	White	Emission:	Direct
Installation:	Recessed, Wall, Suspension, Ceiling		
Environment:	Indoor		

DIMENSIONS

Width:	cm 2.7
Recessed depth:	cm 5.4

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	17W	Service Life:	L70 (6K) 50000h
Type:	0		
Class:	A		

LUMINAIRE

Watt:	17W	Delivered lumens output (lm):	1187lm
		CCT:	3000K
		CRI:	80

Notes

*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. End caps have to be ordered separately. Opal diffusing screen has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

ACCESSORIES



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17901



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17904



240W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000




150W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100




240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - White AQ17201




240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



A.24 - Opal Diffusing Screen - 25m AQ16300



A.24 - Recessed Accessories - Transition Joint - White AQ29001




A.24 - Opal Diffusing Screen - 50m AQ16400



A.24 - Remote Box Power Supply Kit - 313x243x57,5h - (230VAC-48VDC 240W DALI) AQ16000




240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - DALI AQ16801



A.24 - Flexible Opal Diffusing Screen - 10m AQ90000




240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable AQ17801



A.24 - Flexible Opal Diffusing Screen - 25m AQ90100




240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 -




A.24 - Flexible
Opal Diffusing
Screen - 50m
AQ90200



240W Ceiling
power supply kit -
351x61x111H -
230VAC-48VDC
IP20 -
Undimmable -
Black
AQ17304



A.24 - Recessed
Accessories -
Insulating Spacer
(1x)
AQ20601




A.24 - Recessed
Accessories - End
Cap (2x) - White
AQ25001




A.24 - Opal
Diffusing Screen -
10m
AQ16200



150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - White
AQ17701



150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - Black
AQ17704



DALI to DALI-Selv
Interface
103x67x21H
AQ18200