


A.39 Suspension - 1482mm - Direct + Indirect Emission - 3000K - DALI - Silver



IP20 🔲 🐺 CE Dimmerable: +①-

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Controlled emission LED optic System. UGR index control and 65° luminance (EN 12464). Patent-pending proprietary optic system made by a thin black square-meshed grid and by a system of square plano-convex lenses of appropriate beam angle. The internal part of the grid is white painted and has a high reflection coefficient, so that the light incident on the grid is retrieved within the A.39 body. A net 'cut off' at the required angle is obtained through this system. The convex profile of the lens is designed with images optic techniques, so that the emission is limited within the 65° required by standard EN 12464. UGR<19 Angle luminance equals to 65° and beyond: <3,000 cd/m2. The grid positioned over the lenses allows only the rays falling into the required output angular limits to be incident to the lenses. The rays beyond these limits are recovered and redirected inside the light box (if the ray is incident to the white surface) or cancelled (if the ray is incident to the black edge).

FEATURES			
Article Code: Colour: Installation:	AT22405 Silver Suspension, Ceiling	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 148 cm 4.5 cm 8.5		
INCLUDED SOURCES			
Category: Number: Watt: Type: Class: Category: Number: Watt: Type:	LED 1 42W 0 A LED 1 31W 0	Color temperature (K): Color temperature (K): CRI:	3000К 3000К 80
LUMINAIRE			
Watt:	73W	Delivered lumens output (lm) CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	: 6315lm 3000K 61% 86.51lm/W 80 Dali
Notes			

Notes

Screen supplied separately. Screen quantity to order: 1x M186700.



PRODUCT CODE: AT22405

ACCESSORIES

NO IMAGE AVAILABLE			
A.39 - Mechanical			
joint including 1			
suspension cable			
AT09500			

NO IMAGE AVAILABLE	
Screen controll	ed
emission -	

1480mm (5 pcs) AT09900 NO IMAGE AVAILABLE

A.39 - Dimmable Feeding kit including 2 suspension cables (5 poles) 2000m (H) AT10500



End cap kit (2x) -Silver AT09805