


# A.39 Suspension - 2960mm - Direct + Indirect Emission - 3000K - DALI - Silver



IP20 Dimmerable: +0-

#### **TECHNICAL DRAWINGS**



### **DESIGN BY**

Carlotta de Bevilacqua

#### DESCRIPTION

Controlled emission LED optic System. UGR index control and 65° luminance (EN 12464). Patent-pending proprietary optic system made by a thin black square-meshed grid and by a system of square plano-convex lenses of appropriate beam angle. The internal part of the grid is white painted and has a high reflection coefficient, so that the light incident on the grid is retrieved within the A.39 body. A net 'cut off' at the required angle is obtained through this system. The convex profile of the lens is designed with images optic techniques, so that the emission is limited within the 65° required by standard EN 12464. UGR<19 Angle luminance equals to 65° and beyond: <3,000 cd/m2. The grid positioned over the lenses allows only the rays falling into the required output angular limits to be incident to the lenses. The rays beyond these limits are recovered and redirected inside the light box (if the ray is incident to the white surface) or cancelled (if the ray is incident to the black edge).

FEATURES			
Article Code: Colour:	AT24405 Silver	Series:	Indoor
Installation:	Suspension, Ceiling		
DIMENSIONS			
Length:	cm 296		
Width:	cm 4.5		
Height:	cm 8.5		
INCLUDED SOURCES			
Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	82W		
Туре:	0		
Class:	A		
Category:	LED	Color temperature (K):	3000K
Number:	1	CRI:	80
Watt:	67W		
Туре:	0		
LUMINAIRE			
Watt:	149W	Delivered lumens output (lm)	: 12631lm
		CCT:	3000K
		Efficiency:	61%
		Efficacy:	84.77lm/W
		CRI:	80
		Dimmable Typology:	Dali
Notes			

#### <u>Notes</u>

Screen supplied separately. Screen quantity to order: 2x M186700.



## PRODUCT CODE: AT24405

#### ACCESSORIES

NO IMAGE AVAILABLE			
A.39 - Mechanical			
joint including 1			
suspension cable			
AT09500			

NO IMAGE AVAILABLE	
Screen controlle	ed
emission -	
1480mm (5 pcs	)

AT09900

NO IMAGE AVAILABLE

A.39 - Dimmable Feeding kit including 2 suspension cables (5 poles) 2000m (H) AT10500



End cap kit (2x) -Silver AT09805