

A.39 Suspension - Direct + Indirect Emission - 1184mm - 52° - 4000K -Undimmable - 2x4 Optics - Black

DESIGN BY Carlotta de Bevilacqua


DESCRIPTION



IP 20 🔔

Artemide PRODUCT DATA SHEET

TECHNICAL DRAWINGS



FEATURES			
Article Code: Colour: Installation:	BH12904 Black Suspension, Ceiling	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 118 cm 4.5 cm 8.5		
INCLUDED SOURCES			
Category: Number: Watt: Type: Category: Number: Watt:	LED 1 25W 0 LED 1 26W	Color temperature (K): Color Tolerance: Service Life: Color temperature (K): Color Tolerance: Service Life:	4000K MacAdam 2SDCM L90 (20K) 118000h 4000K MacAdam 2SDCM L90 (20K) 118000h
Туре:	0		250 (2011) 11000011
	5014		
Watt:	53W	Delivered lumens output (CCT: Efficiency: Efficacy: CRI:	Im): 4798im 4000K 81% 90.52lm/W 90
Notes			

Screen supplied separately. *Driver uses 1 DALI addres



PRODUCT CODE: BH12904

ACCESSORIES



2x4 optics white AE40001



Angle louvre - 90° corner screen (on same plane) -White BH44001



A.39 -Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400

Louvre - 1184m	nm
Jud optics black	

2x4 optics black AE40004



Angle louvre - 90° corner screen (on same plane) -Black BH44004



A.39 -Suspension/Ceiling - End Caps (2pcs) -Black BH16404

NO IMAGE		
IMAGE	NO	
IIVIAGE	MACT	
	INAGE	

A.39 - Mechanical joint including 1 suspension cable AT09500

		NO)		
	1.0		_		
	IN	1A	Gl	-	
Δ	VA	II.	ΔF	15	F

A.39 -Suspension/Ceiling - Corner (on same plane) - Black BH35004