


# A.39 Suspension - Structural Module 1482mm - Direct + Indirect Emission -4000K - DALI - Black



## **TECHNICAL DRAWINGS**



## **DESIGN BY**

Carlotta de Bevilacqua

### DESCRIPTION

Optimized version in line applications with wide lenghts.Diffusing direct and direct + indirect emission.Recessed trim, trimless, suspension and ceiling versions.Dimmable and non dimmable in two CCT 3000K and 4000K versions.

| FEATURES   |  |  |                          |
|--|--|--|--------------------------|
| Article Code:<br>Colour:<br>Installation:<br>Environment:  | AT22204<br>Black<br>Ceiling<br>Indoor                  | Series:  | Indoor                   |
| DIMENSIONS   |  |  |                          |
| Length:<br>Width:<br>Height:   | cm 148<br>cm 4.5<br>cm 8.5                             |  |                          |
| INCLUDED SOURCES   |  |  |                          |
| Category:<br>Number:<br>Watt:<br>Type:<br>Class:<br>Category:<br>Number:<br>Watt:<br>Type:<br>Class: | LED<br>1<br>42W<br>0<br>A<br>LED<br>1<br>31W<br>0<br>A | Color temperature (K):<br>Color temperature (K): | 4000К<br>4000К           |
| LUMINAIRE  |  |  |                          |
| Watt:  | 42W + 31W  | Delivered lumens output (lm):<br>CCT:            | 2472lm + 4118lm<br>4000K |

CRI:

**Dimmable Typology:** 

80

Dali



#### ACCESSORIES

