


# A.39 Suspension/Ceiling - 1482mm - Direct Emission - 3000K - DALI - Silver



IP20 Dimmerable: +0-

#### **TECHNICAL DRAWINGS**



## **DESIGN BY**

Carlotta de Bevilacqua

## DESCRIPTION

Controlled emission LED optic System. UGR index control and 65° luminance (EN 12464). Patent-pending proprietary optic system made by a thin black square-meshed grid and by a system of square plano-convex lenses of appropriate beam angle. The internal part of the grid is white painted and has a high reflection coefficient, so that the light incident on the grid is retrieved within the A.39 body. A net 'cut off' at the required angle is obtained through this system. The convex profile of the lens is designed with images optic techniques, so that the emission is limited within the 65° required by standard EN 12464. UGR<19 Angle luminance equals to 65° and beyond: <3,000 cd/m2. The grid positioned over the lenses allows only the rays falling into the required output angular limits to be incident to the lenses. The rays beyond these limits are recovered and redirected inside the light box (if the ray is incident to the white surface) or cancelled (if the ray is incident to the black edge).

FEATURES			
Article Code: Colour: Installation:	AT14405 Silver Suspension, Ceiling	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 148 cm 4.5 cm 8.5		
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 42W 0 A	Color temperature (K):	3000K
LUMINAIRE			
Watt:	42W	Delivered lumens output (lm) CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	: 2374lm 3000K 41% 56.52lm/W 80 Dali
Netos			


#### Notes

Screen supplied separately. Screen quantity to order: 1x M186700.



# PRODUCT CODE: AT14405

## ACCESSORIES



We reserve the right to change our product specifications. Please visit www.artemide.com for the latest product information