

A. Sharping Wired Gear Plates Sharping LED Direct Emission + Indirect - 1184mm 64W 52° 4000K



IP20  Dimmerable: 


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Algoritmo Sharping is very flexible and it allows to combine in continuity Sharp light modules, with indirect and diffused LED lighting in warm white (3000K) and neutral white (4000K). Structural modules are in extruded aluminum, available in different lengths depending on the installation option, three finishes (white, black, silver or gloss anodized), two optic finishes (black and white) and three beams (20°, 36° and 52°).

TECHNICAL DRAWINGS



FEATURES

Article Code:	AE17200	Series:	Indoor
Colour:	White		
Installation:	Recessed, Wall, Suspension, Ceiling		
Environment:	Indoor		

DIMENSIONS

Length: cm 118

INCLUDED SOURCES

Category:	LED	Color temperature (K):	4000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	64W	Service Life:	L90 (20K) 118000h
Type:	0		
Class:	A		

LUMINAIRE

Watt:	64W	Delivered lumens output (lm):	5156lm
		CCT:	4000K
		Efficiency:	75%
		Efficacy:	80.56lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

MV integrated through-cable. Protection screen for indirect LED wired plate included.