


# Algoritmo Controlled-Prismoptic Emission - Wired gear plates white LED Double emission - 122W 2368mm 4000K DALI + Prismoptic Optic



Dimmerable: + -

## DESIGN BY

Carlotta de Bevilacqua, Paola di Arianello

## DESCRIPTION

A modular system for ceiling or wall-recessed installation, to be installed as a continuous line or with angles, composed of structural modules in extruded aluminium, of pre-wired gear plates with through-wiring and quick-connection system of optics systems and components for connecting, fixing, joining or finishing the system. The prewired LED plates were designed for diffused emission, wall washer light, prismoptic or controlled emission, for projectors integration (PAD or Cube 37), for 3 phase track alimentation. Complies with standard EN60598-1 and any other specific standard.

## FEATURES

<b>Article Code:</b>	M2885N01 M197000	<b>Series:</b>	Indoor
<b>Installation:</b>	Recessed, Wall, Suspension, Ceiling		

## DIMENSIONS

<b>Length:</b>	cm 236
<b>Weight:</b>	kg 2

## INCLUDED SOURCES

<b>Category:</b>	LED	<b>Color temperature (K):</b>	4000K
<b>Number:</b>	1		
<b>Watt:</b>	122W		
<b>Type:</b>	0		
<b>Class:</b>	A		

## LUMINAIRE

<b>Watt:</b>	122W	<b>Delivered lumens output (lm):</b>	10475lm
		<b>CCT:</b>	4000K
		<b>Efficiency:</b>	66%
		<b>Efficacy:</b>	85.86lm/W
		<b>CRI:</b>	80
		<b>Dimmable Typology:</b>	Dali

## Notes

MV integrated through-cable. \* Direct e indirect emission dimmable Protection screen for indirect cabled LED plate included. Occupies 2 Dali destination


**ACCESSORIES**




Electronic power supply. IP67. Input voltage range: 90-264VAC / 47-63Hz. Output voltage: 48VDC. Protection against overcurrent, overvoltage, short-circuit and overtemperature, with automatic restart. - 240W. For feeding up to a total 225W. 244x68x39mm. M075100



Electrical connector (only for RGB LED) to couple wall-surface or floor-recessed LED Algoritmo System modules, powered through the same electrical circuit. M221900



Algoritmo System LED - Optics - Prismoptic - 2368mm M197000



Supply Kit. Allows for connection of the mains to the first pre-wired gear plate of the initial module. To be used only with recessed and surface installation. - MV (7xmax 1,5 mm<sup>2</sup>) To power white LED plates and accent modules. M073240



Supplementary through-wiring (optional). To be used in mixed configuration with LV and MV pre-cabled gear trays. - MV 2368mm. M198900



Control Interface. Form managing groups of Algoritmo System LED RGB and/or white LED/RGB Algoritmo Floor lighting units. Integrated sequencer for stand-alone operation with predefined color sequence. Possibility of master-slave configuration. DALI DMX light management systems are not included. - Compatible DALI 310X168X90 mm. IP67 M077000



Control Interface. Form managing groups of Algoritmo System LED RGB and/or white LED/RGB Algoritmo Floor lighting units. Integrated sequencer for stand-alone operation with



Supplementary through-wiring (optional). To be used in mixed configuration with LV and MV pre-cabled gear trays. - LV 2368mm. M199000



Electronic power supply. IP67. Input voltage range: 90-264VAC / 47-63Hz. Output voltage: 48VDC. Protection against overcurrent, overvoltage, short-circuit and overtemperature, with automatic

predefined color sequence.  
Possibility of master-slave configuration.  
DALI DMX light management systems are not included. -  
Compatible DALI.  
Suitable for DIN rail mounting.  
106x90x70 mm.  
IP20  
M077200



Electronic power supply. IP67. Input voltage range: 90-264VAC / 47-63Hz. Output voltage: 48VDC. Protection against overcurrent, overvoltage, short-circuit and overtemperature, with automatic restart. 100W. For feeding up to a total 90W. 220x68x38mm.  
M075000

restart. - 320W.  
For feeding up to a total 300W.  
252x90x44mm.  
M076100



Movement detector - 296mm  
DALI  
M2981



Control Interface. Form managing groups of Algoritmo System LED RGB and/or white LED/RGB Algoritmo Floor lighting units. Integrated sequencer for stand-alone operation with predefined color sequence. Possibility of master-slave configuration. DALI DMX light management systems are not included. -  
Compatible DALI or DMX  
310X168X90 mm.  
IP67  
M077100



Control Interface. Form managing groups of Algoritmo System LED RGB and/or white LED/RGB Algoritmo Floor lighting units. Integrated sequencer for stand-alone operation with predefined color sequence. Possibility of master-slave configuration. DALI DMX light management systems are not included. -  
Compatible DALI or DMX. Suitable for DIN rail mounting.



Supply Kit. Allows for connection of the mains to the first pre-wired gear plate of the initial module. To be used only with recessed and surface installation. - LV (3xmax 1,5 mm2)  
To power LED RGB trays.  
M073230

106x90x70 mm.  
IP20  
M077300