PRODUCT DATA SHEET PRODUCT CODE: M2910N20

# Algoritmo Stand-Alone - Suspension - LED diffused emission - Direct emission - 34W 4000K Non dimmable - White




#### **DESIGN BY**

Carlotta de Bevilacqua, Paola di Arianello

#### **DESCRIPTION**

Series of single units, preconfigured and complete for suspension-mounting, wall-mounting and ceiling-mounting. Body in extruded aluminium, painted white. Two lengths available: 1188 mm and 2372mm. LED version direct emission, diffused: LED monochromatic warm white (3000 K) and neutral white (4000 K). Power supply and light management system included, non dimmable or Dali-SwitchDim. Suspended version direct or double emission. Luminaires come complete with end caps, fixing brackets or suspension cables and optics. Compliant with standard EN60598-1 and other specific standards.

## **TECHNICAL DRAWINGS**



| EATURES      |     |
|--------------|-----|
|              |     |
| utiala Cadas | MAD |

| Article Code: | M2910N20   | Material: | Extruded Aluminium |
|---------------|------------|-----------|--------------------|
| Colour:       | White      | Series:   | Indoor             |
| Installation: | Suspension | Emission: | Direct/indirect    |
| Environment:  | Indoor     |           | Diffused & Dark    |
|               |            |           | Light              |

#### **DIMENSIONS**

| Length: | cm 118 | Glow Wire Test: |
|---------|--------|-----------------|
| Width:  | cm 4.5 |                 |
| Height: | cm 11  |                 |
| Weight: | kg 3.8 |                 |

## **INCLUDED SOURCES**

| Category: | LED | Color temperature (K): | 4000K           |
|-----------|-----|------------------------|-----------------|
| Number:   | 1   | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 34W | Service Life:          | L70 (4K) 60500h |
| Туре:     | 0   |                        |                 |
| Class:    | Α   |                        |                 |

### **LUMINAIRE**

| Watt: | 34W | Delivered lumens output (lm):2053lm |           |
|-------|-----|-------------------------------------|-----------|
|       |     | сст:                                | 4000K     |
|       |     | Efficiency:                         | 45%       |
|       |     | Efficacy:                           | 60.38lm/W |
|       |     | CRI:                                | 80        |

#### Notes

Upper screen in PMMA included.

850°