

Aria Mini - 6W 3000K - IP65 - White




IP65 💮

DESCRIPTION

Light fixture with high-performance LED light sources. Wall or ceiling installation. Composed by: frame, body, asymmetrical reflector, fixing springs or housing. Body in injection mould of aluminium. Frame in aluminium. Body and frame are painted with outdoor treatment three stages: nanotechnologies, antioxidant primer, polyester paint. Metalized polycarbonate reflector. Silicone gasket. Protection screen in tempered glass, 3mm-thick. Housing in bend metal. Electrical connection to the ballast by means of a cable with appropriate terminal board supplied with the fixture. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K IP Rating IP65 or IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

TECHNICAL DRAWINGS



FEATURES

Article Code: Colour: Installation: Environment:	AJ10001 White Wall, Ceiling Outdoor	Material: Series:	Aluminum, polycarbonate, tempered glass Outdoor
DIMENSIONS			
Length: Height: Weight: Recessed depth:	cm 10 cm 10 kg 0.6 cm 4.8	Cutout shape:	Squared
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 6W 0 A	Color temperature (K):	3000K
LUMINAIRE			
Watt:	6W	Delivered lumens output (lm): 215lm	

CCT:

CRI:

Efficiency:

Efficacy:

3000K

35.87lm/W

37%

85



ACCESSORIES

NO IMAGE AVAILABLE

ALIMENT. 8,4W 350mA (indip.) NL19032

> NO IMAGE AVAILABLE

ALIMENT. 20W 700mA (indip.) NL19036

NO IMAGE AVAILABLE

Area Mini Cassaforma AJ90000 NO IMAGE AVAILABLE

ALIMENT. 12W 700mA IP67 NL19024

> NO IMAGE AVAILABLE

ALIMENT. 35W 700mA IP67 NL19029 NO IMAGE AVAILABLE

ALIMENT. 5W 350mA IP67 NL11022

> NO IMAGE AVAILABLE

ALIMENT. 9,8W 700mA (indip.) NL19035