PRODUCT DATA SHEET PRODUCT CODE: M036226

## Chocolate Floor - LED 1-desk 3000K Interactive-Dali - White



# IP20 Dimmerable: +0-


#### **DESIGN BY**

a.g Licht

## **DESCRIPTION**

Chocolate Floor Led sets new standards in the lighting and living at the workplace, and features unique characteristics in terms of ergonomics, efficiency and lighting comfort. With the innovative optics technology, the direct light is directed and focused onto the specific visual task, for single desk (800 x 1600 mm) or double desk workstation(1600 x 1600 mm). It provides maximum efficiency thanks to a large direct component (48%, 2-desk version). 2 light management options: Dimmable (double-switch circuit), Interactive-Dali System with movement detector and daylight sensor, providing auto-regulation of the light intensity depending on the light level in the environment, and people presence.

## **TECHNICAL DRAWINGS**



## **FEATURES**

| Article Code: | M036226 | Material:      | Aluminium and Steel |
|---------------|---------|----------------|---------------------|
| Colour:       | White   | Series:        | Indoor              |
| Installation: | Floor   | Area contract: | Office              |
| Environment:  | Indoor  | Emission:      | Direct/indirect     |
|               |         |                |                     |

#### **DIMENSIONS**

| Length: | cm 59.3 |
|---------|---------|
| Width:  | cm 25.5 |
| Height: | cm 190  |
| Weight: | kg 14   |

## **INCLUDED SOURCES**

| Category:                            | LED | Color temperature (K): | 3000K          |
|--------------------------------------|-----|------------------------|----------------|
| Number:                              | 1   | Color Tolerance:       | MacAdam 4SDCM  |
| Watt:                                | 26W | CRI:                   | >80            |
| Delivered lumens output (lm): 2510lm |     | Efficacy:              | 96lm/W         |
| Туре:                                | 0   | Service Life:          | L70(6K)>36000h |
| Class:                               | A   |                        |                |
| Category:                            | LED | Color temperature (K): | 3000K          |
| Number:                              | 1   | Color Tolerance:       | MacAdam3SDCM   |
| Watt:                                | 44W | CRI:                   | >80            |
| Delivered lumens output (lm): 3902lm |     | Efficacy:              | 89lm/W         |
| Туре:                                | 0   | Service Life:          | L70(6K)>36000h |
| Class:                               | Α   |                        |                |

#### **LUMINAIRE**

| Power Supply: | Electronic Interactive- Delivered lumens output (lm): 5386lm |             |           |  |
|---------------|--|-------------|-----------|--|
|               | Dali Integrated  | CCT:        | 3000K     |  |
| Watt:         | 81.0W  | Efficiency: | 100%      |  |
| Voltage:      | 220V-240V  | Efficacy:   | 66.49lm/W |  |
|               |  | CBI.        | 80        |  |



## PRODUCT DATA SHEET

## **ACCESSORIES**



INTERACTIVE-DALI remote control. M104900