


Demetra LED white table - Body 3000K



IP20 💮 🌋 🕅 🕑 😢 CE Dimmerable: + **0**-

TECHNICAL DRAWINGS



DESIGN BY

Naoto Fukasawa

DESCRIPTION

A selection of table lamps (with table base, clamp and fixed support), also available in the reading, wall and spot versions.Materials: head and arms in painted aluminium.Specification: fully adjustable, turnable and tilting arms and diffuser, plus the LED sources integrated into its head.Demetra MD: this table model features a Motion Detector option detecting moving objects and people and turning the light on or off accordingly.

Article Code:1734020AColour:WhiteInstallation:TableDIMENSIONS	Material: Series: Area contract: Emission: Max Extension Length: Impact Resistance: Glow Wire Test: Color temperature (K):	aluminium, technopolymer, steel Design Hospitality, Residential Direct and adjustable light cm 100 N.D. 750
Installation:TableInstallation:TableDIMENSIONSLength:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Vatt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIRE8W	Area contract: Emission: Max Extension Length: Impact Resistance: Glow Wire Test:	Design Hospitality, Residential Direct and adjustable light cm 100 N.D.
DIMENSIONSLength:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCEScm 102Category:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIRE8W	Area contract: Emission: Max Extension Length: Impact Resistance: Glow Wire Test:	Hospitality, Residential Direct and adjustable light cm 100 N.D.
Length:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIRE8W	Max Extension Length: Impact Resistance: Glow Wire Test:	Residential Direct and adjustable light cm 100 N.D.
Length:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Max Extension Length: Impact Resistance: Glow Wire Test:	light cm 100 N.D.
Length:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Impact Resistance: Glow Wire Test:	light cm 100 N.D.
Length:cm 31Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Impact Resistance: Glow Wire Test:	N.D.
Width:cm 20Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Impact Resistance: Glow Wire Test:	N.D.
Height:cm 35Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Glow Wire Test:	
Base Diameter:cm 20Max Extension Height:cm 102INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W		750
Max Extension Height: cm 102 INCLUDED SOURCES Category: LED Number: 1 Watt: 6W Delivered lumens output (Im): 726Im Type: 0 Class: A LUMINAIRE Watt: 8W	Color temperature (K):	
INCLUDED SOURCESCategory:LEDNumber:1Watt:6WDelivered lumens output (Im):726ImType:0Class:ALUMINAIREWatt:8W	Color temperature (K):	
Category:LEDNumber:1Watt:6WDelivered lumens output (lm):726lmType:0Class:ALUMINAIREWatt:8W	Color temperature (K):	
Number: 1 Watt: 6W Delivered lumens output (Im): 726Im Type: 0 Class: A LUMINAIRE Watt: 8W	Color temperature (K):	
Watt: 6W Delivered lumens output (Im): 726Im Type: 0 Class: A LUMINAIRE Watt: 8W	color temperature (it).	3000K
Delivered lumens output (Im): 726lm Type: 0 Class: A LUMINAIRE Watt: 8W	Color Tolerance:	MacAdam 2SDCM
Type: 0 Class: A LUMINAIRE 8W	CRI:	90
Class: A LUMINAIRE Watt: 8W	Efficacy:	120lm/W
LUMINAIRE Watt: 8W	Service Life:	50000-L70
Watt: 8W		
	Delivered lumens output (lm	: 385lm
Voltage: 100-240V	сст:	3000K
-	Efficiency:	54%
	Efficacy:	48.08lm/W
		90
	CRI:	
Notes	CRI: Dimmer Typology:	Microswitch Dimmer

Microswitch dimmer



ACCESSORIES



BASE BCO 1733020A





DEMETRA SUPPORTO T FISSO BCO 1743020A