
PRODUCT DATA SHEET PRODUCT CODE: T42012LW20

Effetto 14 Square 2 large beams Anthracite gray



IP65 □ **⑤** ▼


DESIGN BY

Ernesto Gismondi

DESCRIPTION

Light fixture with 2 light beams using monochromatic LED light sources caracterized by warm colour temperature (3000K) together with light-diffusing lenses which optimize the optical performance of the beams and establish their width. Designed to create geometric lights of scenic effect, it has 2 large beams of 90°. Wall installation. Composed by lighting cap unit and terminal board fixed together by means of locking dowels. Cap in die-cast EN AB-47100 aluminium. Terminal board in reinforced polymer. Watertight gasket in silicone rubber. Locking dowels used outside the fixture in AISI 316 stainless steel. PMMA lenses siliconed flush with the cap to obtain the beam angle opening.

TECHNICAL DRAWINGS



FEATURES

I L/ (I O I L D			
Article Code: Colour: Installation: Environment:	T42012LW20 Anthracite gray Wall Outdoor	Material: Series: Area contract:	Aluminum, composite technopolymer, methacrylate Outdoor Urban, Outdoor,
		Emission:	Residential Indirect
DIMENSIONS			
Length: Width: Height:	cm 14 cm 14 cm 14	Impact Resistance: Glow Wire Test:	IK10 650

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	4SDCM
Watt:	7W	CRI:	80 typ
Delivered lumens output (lm):357lm		Efficacy:	85lm/W
Туре:	0	Service Life:	L70(14K)>81600
Class:	A		

LUMINAIRE

Power Supply:	Electronic Integrated Delivered lumens output (lm):109lm		
Watt:	7W	CCT:	3000K
Voltage:	220V-240V	Efficiency:	100%
		Efficacy:	15.57lm/W
		CRI:	80

Notes

Wiring to be carried out inside the terminal board by piercing an IP65 membrane grommet suitable for cables with a diameter of 6-13 mm. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Effective power 5,4W.



