
PRODUCT DATA SHEET PRODUCT CODE: T42004NW20

Effetto 14 Square 4 narrow beams Anthracite gray



IP65 □ **⑤ ⑤**


DESIGN BY

Ernesto Gismondi

DESCRIPTION

Light fixture with 4 light beams using monochromatic LED light sources caracterized by warm colour temperature (3000K) together with light-diffusing lenses which optimize the optical performance of the beams and establish their width. Designed to create geometric lights of scenic effect, it has 4 narrow beams of 15°. Wall installation. Composed by lighting cap unit and terminal board fixed together by means of locking dowels. Cap in die-cast EN AB-47100 aluminium. Terminal board in reinforced polymer. Watertight gasket in silicone rubber. Locking dowels used outside the fixture in AISI 316 stainless steel. PMMA lenses siliconed flush with the cap to obtain the beam angle opening.

TECHNICAL DRAWINGS



FEATURES

FEATURES			
Article Code: Colour: Installation: Environment:	T42004NW20 Anthracite gray Wall Outdoor	Material:	Aluminum, composite technopolymer, methacrylate
		Series:	Outdoor
		Area contract:	Urban, Outdoor,
			Residential
		Emission:	Indirect
DIMENSIONS			
Length:	cm 14	Impact Resistance:	IK10
Width:	cm 14	Glow Wire Test:	650
Height:	cm 14		

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	4SDCM
Watt:	11W	CRI:	80 typ
Delivered lumens output (Im):714lm		Efficacy:	85lm/W
Type:	0	Service Life:	L70(14K)>81600
Class:	Α		

LUMINAIRE

Power Supply:	Electronic Integrated Delivered lumens output (lm): 76,1lm		
Watt:	11W	CCT:	3000K
Voltage:	220V-240V	Efficiency:	100%
		Efficacy:	6.92lm/W
		CRI:	80

Notes

Wiring to be carried out inside the terminal board by piercing an IP65 membrane grommet suitable for cables with a diameter of 6-13 mm. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Effective power 10,8W.



PRODUCT DATA SHEET



