LineaLed Wallwasher 8,5W - 28° 3000K



IP65/67 ♠ ▼

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Walk-over and drive-over recessed floor installation. Composed by body in extruded aluminium, protection glass; provided with junction box


for input/output connection. Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 10 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

TECHNICAL DRAWINGS



FEATURES

Article Code: Colour:	NL1732025K0 Silver gray	Material:	Aluminium,transparei tempered glass.
Installation:	Recessed	Series:	Outdoor
		Area contract:	Outdoor
DIMENSIONS			
Length:	cm 30	Impact Resistance:	IK07
Width:	cm 4.8		
Height:	cm 9		
Weight:	kg 0.9		

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K	
Number:	1	Voltage:	24Vdc	
Watt:	8,5W			
Delivered lumens output (lm): 1776lm				
Type:	0			

LUMINAIRE

Power Supply:	Elettronic	Delivered lumens output (lm):	411lm
Watt:	8,5W	CCT:	3000K
Voltage:	24 Vdc	CRI:	80

Notes

Class:

Ottica Medium

Medium luminous flux to highlight details, large sections of windows.(25° optic)



ACCESSORIES

NO IMAGE AVAILABLE

Housing end cap (pair) - 46,5 x 62,5 x 1,5mm NL76750

NO IMAGE AVAILABLE

Housing L=982mm NL76700

NO IMAGE AVAILABLE

Cassaforma L=780mm NL76710

> NO IMAGE AVAILABLE

ALIMENT. 70W 24Vdc IP67 NL89080 NO IMAGE AVAILABLE

Female power connector for discontinuos connection NL19023

> NO IMAGE AVAILABLE

Cassaforma L=300mm NL76740

> NO IMAGE AVAILABLE

ALIMENT. 40W 24Vdc IP67 NL62040

> NO IMAGE AVAILABLE

ALIMENT. 150W 24Vdc IP67 NL62880 NO IMAGE AVAILABLE

Male power connector for discontinuos connection NL19021

> NO IMAGE AVAILABLE

Cassaforma L=500mm NL76730

> NO IMAGE AVAILABLE

CONNETTORE ALIMENTAZIONE + TAPPO NL19052



LINEALED STAFFA GIUNZIONE C/CASSA NL75810