


Megara 90 3000K - 3 beams



IP65/67




DESIGN BY

Michele De Lucchi

DESCRIPTION

Light fixture with high-performance LED light sources. Drive-over recessed floor installation with floorprotruding cap. All the versions are drive-over up to 5000Kg. Due to the low height of the cap, Megara 90 is also suitable for installation in walk-over areas, being careful to avoid areas of direct transit (near walls, buildings, etc.) 3 sizes (90, 150, 220 mm).Composed by body, cap, diffuser, recessing box.Body and cap in painted EN AB44100 aluminium, silicone gaskets; provided with 30 cm-long pre-resined three-pole connection cable (H07RN-F for versions 90 qnd 150, H05RN-F for version 220).Electronic ballast integrated in the body.Diffuser in UV resistant polycarbonate.Power connection to the mains by means of the IP67 connector supplied with the light fixture, which can be housed in the recessing box and is suitable for cables with a diameter from 5 to13.3 mm.Fixing to the recessing box is ensured by means of anti-vandal screws TORX.Recessing box for laying in reinforced polymer to be ordered separately.Radial emission beam optic.1, 2, 4 beam and full configurations.White monochromatic LEDs available in 3 colour temperatures:Warm = 3000KNeutral = 4000KCold = 6000KScrews in AISI 316 stainless steel.Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint.Technical features of light fixtures in compliance with EN60598-1 and part 2-13.IP Rating IP65-IP67.ENEc approved.Insulation class I.

TECHNICAL DRAWINGS



FEATURES

Article Code:	T415100W00	Material:	Painted die-cast aluminium with 3-stage outdoor treatment
Colour:	Anthracite grey	Series:	Outdoor
Installation:	Recessed	Area contract:	null
Environment:	Outdoor		

DIMENSIONS

Height:	cm 2.3	Cutout diameter:	cm 19
Depth:	cm 10.1	Cutout shape:	Rounded
Recessed depth:	cm 10.1	Impact Resistance:	IK10
		Glow Wire Test:	NA

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	CRI:	80 typ
Watt:	3W		
Delivered lumens output (lm):	6lm		
Type:	0		
Class:	A		

LUMINAIRE

Watt:	2.4W	Delivered lumens output (lm):	15lm
Voltage:	220V-240V	CCT:	3000K
		Efficiency:	100%
		Efficacy:	6.33lm/W
		CRI:	80

ACCESSORIES



Recessing box
T409907